

Millennium Plus 70

DOOR

Flush entrance pedestrian door system with 70 mm of frame depth that guarantees high thermal and acoustic insulation.



Sightlines

Frame 70 mm, Sash 70 mm

Polyamide Strip Length

24 mm

Profile Thickness

Door 2,0 mm

Glazing

Max. 54 mm, Min. 15 mm

Maximum Sash Dimensions

Door:

Width (L) 1800 mm, Height (H) 3000 mm

Concealed door hinges:

Width (L) 1500 mm, Height (H) 2700 mm








Maximum Sash Weight

220 kg


120 Kg (concealed hinges)

Consult maximum weight and dimensions according to typologies


FEATURES

Transmittance		$U_w \geq 0,9$ (W/m ² K)
Acoustic insulation		Rw up to 38 dB
Air permeability		Class 4
Water tightness		Class 6A
Wind resistance		Class C4
Resistance to mild impact		Class 5 (máx.)
Repeated opening and closings		1.000.000 cycles

Wind resistance: Reference test 1,20 x 2,30 m / 1 sash
 Resistance to mild impact: UNE-EN 13049. Test on door reference 1,80 x 2,20 m / 2 sashes. Laminated glass 3+3
 Resistance to repeated openings and closings: UNE-EN 1191. Test on door reference 2,1 X 2,2 m / 2 sashes



OPENING POSSIBILITIES



Inward Opening

Side hung

Outward opening

Side hung

Automatic Opening

Outward and inward side hung

Swing Opening

Side hung

POSSIBILITIES

